



1L - 5 L 1L

WOLF MASTERLUBE SYNFLOW DC 5W40/5W30

Synthetic "Long Life" engine oil of the latest generation. Satisfies the most recent requirements of the passenger car manufacturers. Suitable for all types of modern gasoline or diesel engines, also those with direct fuel injection.

API SL/CF - ACEA A3/B3/B4 - MB 229.3 - VW 502.00/505.00
5W40: also BMW LONGLIFE - GM-LL-B-025



1L

WOLF MASTERLUBE SYNFLOW PI 5W40

Synthetic based engine oil, particularly for use in high-powered diesel engines of passenger cars. Due to its special composition, it is suitable for diesel engines with pump-injector units. Can also be used in all modern gasoline engines.

API SJ/CF - ACEA A3/B3 - MB 229.1 - VW 500.00/505.00/505.01



1L - 2 L - 5 L

WOLF MASTERLUBE GTS B4 10W40

Advanced synthetic based motor oil for optimal protection in all driving conditions. Suitable for all gasoline or diesel engines of passenger cars : fuel injection, turbo or multi-valve. Especially adapted for modern diesel engines with direct fuel injection (common rail).

API SL/CF - ACEA A3/B3/B4 - MB 229.1 - VW 500.00/505.00



1L - 2 L - 5 L

WOLF MASTERLUBE EX PLUS 15W40

Very high quality, mineral engine oil for use in actual engines of passenger cars and light vans. Suitable for most gasoline and diesel engines, with or without turbo. Protects the engine and the exhaust catalyst.

API SL/CF - ACEA A3/B3 - MB 229.1 - VW 501.01/505.00



1L - 5 L 1L - 5 L

WOLF SUPER MULTI ISODYNAMIC 20W50/15W40

Lubricating oil for gasoline and light diesel engines without turbo compression. This oil ensures a good protection against wear and corrosion.

API SF/CC - CCMC G2/D1



1L

WOLF TWO STROKE SYNFLOW 2T

100% synthetic two-stroke engine oil. Perfect blending with the fuel, high lubrication power and very low smoke formation. Suitable for all modern two-stroke engines, with the exception of outboard engines.

API TC - JASO FC



1L

WOLF TWO STROKE SEMI-SYNTHETIC 2T

Semi-synthetic two-stroke motor oil, meeting the most stringent requirements from engine manufacturers. Reinforced anti-wear action and exceptional detergent power. For fuel mixing or direct injection.

API TC - JASO FB



1L

WOLF TWO STROKE UNIVERSAL 2T

Universal two-stroke engine oil for use in motorcycles, motorbikes, chainsaws, lawn mowers, etc. Prediluted for ease of mixing and also suitable for systems with direct injection. Colored red.

API TC



1L

WOLF TWO STROKE OUTBOARD 2T

Special motor oil for all water-cooled two-stroke engines. Ashless formulation for use in outboard engines, jet-ski, water scooters and snowmobiles. Blue colored.

API TD - NMMA TC-W3



1L 1L

WOLF AGRIFLOW 4T 15W40/SAE 30

High performance four-stroke engine oil for use in engines of lawnmowers and other small auxiliary engines.

API SG - CCMC G4



1L

WOLF AGRIFLOW 2T

High performance two-stroke oil for all gardening equipment, chain saws, etc.

API TC - JASO FB



2 L

WOLF AGRIFLOW LOW SMOKE 2T

Specially formulated two-stroke motor oil, which meets the requirements for reduced smoke formation. Particularly adapted for intensive use for hobby, garden, etc.

API TC - JASO FC



WOLF OIL CORPORATION NV® 2005

Georges Gilliotstraat 52
2620 Hemiksem - Belgium
Tel. +32 3 870 00 00
Fax +32 3 870 00 99

info@wolfoil.com
www.wolfoil.com



1L

WOLF SPECIAL HD POLYGEAR GL5 75W90

Semi-synthetic transmission and rear-axle oil for cars. Specially adapted for "hard" gear boxes. Exceptional anti-wear properties.

API GL 5 - MIL-L-2105 C,D



1L

WOLF SPECIAL POLYGEAR G50 75W90

Fully synthetic lubricant for gearboxes with integrated differential of front-wheel drive cars. Guarantees exceptional oil and transmission lifetime. Exceeds the requirements of API GL-4 for gearbox oils.

API GL 4+ - MIL-L-2105 - VW 501.50



1L

WOLF HD POLYGEAR GL5 80W90

Widely applicable transmission oil for hypoid rear axles of all vehicles. Excellent protection against mechanical and corrosive wear of gear assemblies, even under shockloading.

API GL 5 - MIL-L-2105 C,D



1L

WOLF HD POLYGEAR GL5 75W80W

Special, hypoid type transmission oil for front-wheel driven vehicles requiring a low viscosity (SAE 75W80W) lubricant. Excellent protection of gears against wear and corrosion.

API GL 5 - MIL-L-2105 C,D



1L

WOLF ATF DIII

Extremely stable automatic transmission fluid for cars, buses and off-highway equipment. Also suitable for powershift transmissions, power steering and vehicle hydraulic systems. Excellent fluidity at low temperature.

GM DEXRON III - FORD MERCON - MB 236.1 and 5



1L

WOLF ATF DII

Universal automatic transmission fluid, meeting the General Motors Dexron II specification. Can also be used in power steering systems, where this specification is recommended.

GM DEXRON II - FORD M2C-166H - MB 236.7



1L

WOLF CENTRAL HYDRAULIC FLUID CHF

Special hydraulic fluid for centralised systems in vehicles : power steering, levelling systems, hydrodynamic suspension, shock absorbers.



1L

WOLF MINERAL FLUID LHM

Mineral hydraulic fluid to be used in hydraulic systems, brake circuits and oleo pneumatic suspensions of CITROEN vehicles, where the components are painted green. Miscible with other mineral hydraulic fluids with designation LHM. Not miscible and not compatible with older fluids of the LHS2 type.



1L

WOLF BRAKE FLUID DOT 5.1

Universal synthetic brake fluid which supersedes the requirements of the Federal Motor Vehicle Safety Standard n°116 - DOT 5.1. Higher wet boiling point and better fluidity at low temperature. Specially recommended for use in competitive driving and in ABS or ASR brake systems. This product may not be mixed with brake fluids of the silicone type (purple colour) or silicate esters.



1L - 5L

WOLF BRAKE FLUID DOT 4

Synthetic fluid with high boiling point for hydraulic brakes and clutches. Exceeds SAE J 1703 F and FMVSS DOT 4 specifications. This product is completely miscible with all brake fluids meeting DOT 3 or DOT 4 specifications.

