

S.T.O.U. SF/CE SAE 10W40

DESCRIPTION :

Universal multigrade oil for engines, transmissions, wet brakes and hydraulic systems of agricultural tractors. Therefore a single oil can be used for the lubrication of different tractor parts.

APPLICATIONS:

This oil is recommended for the lubrication of charged or non-charged diesel engines, 4-stroke petrol and LPG engines. This oil is optimized for the lubrication of gearboxes, rear axles, final drives, power take-offs, wet brakes, hydraulic systems of agricultural tractors and off-road equipment.

SPECIFICATION LEVEL:

API	CF-4, CE/SF GL 4, GL 5 (low speed/ high torque)	MASSEY FERGUSON	M-1127 M-1135 M-1139 M-1144
ACEA	E2/E3	CATERPILLAR	TO-2
MB	227.1	CASE NEW HOLLAND	MAT 3525, 3526
MAN	271	ALLISON	C-4
FORD	ESN-M2C-159 B/C ESN-M2C-121 C ESN-M2C-86 A/B ESN-M2C-134 C/D	ZF	TE-ML 06B, 07B

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			10W40
Density at 15°C	D 4052	kg / m ³	875
Viscosity at 40°C	D 445	cSt	96
Viscosity at 100°C	D 445	cSt	14,1
Viscosity at -25°C	D 5293	cP	7000
Viscosity index	D 2270		150
Pour point	D 6892	°C	-35
TBN	D 2896	g KOH/kg	10,7
Flash point COC	D 92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.