

MULTICHANTIER 10W40

DESCRIPTION :

Multipurpose oil for use in public works. It meets the specifications of most manufacturers, both in terms of engine oils and gear oils. Its high viscosity index allows the use in all weather conditions. This type of oil is sometimes referred to as CPO = Contractors Plant Oil

APPLICATIONS:

Diesel engines with or without turbo and 4-stroke petrol engines. Without limitation recommended for all uses in the area of off-road equipment. Motors, mechanical transmissions, transaxles, hydraulic systems, wet brakes and compressors, pumps, reductions...

SPECIFICATION LEVEL :

Engines	API CE/CF/CF-4/SF MIL-L-2104 D MB 227.1 ACEA E2	SAE 10W40
Tractors	FORD M2C 159B MF M-1139, M-1144, M-1145 JOHN DEERE J20A, J27	
Transmissions	API GL 4/5, low speed/high couple ALLISON C3, C4 CATERPILLAR TO-2 ZF TE-ML 06B, C, D ZF TE-ML 07B powershift transmissions NH 526C	SAE 80W90
Hydraulics	VICKERS DENISON HF-O	
Compressors	COMPAIR HYDROVANE / ATLAS COPCO	

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			10W40
Density at 15°C	D 4052	kg / m ³	878
Viscosity at 40°C	D 445	cSt	100
Viscosity at 100°C	D 445	cSt	14,8
Viscosity at -25°C	D 5293	cP	6550
Viscosity index	D 2270		154
Pour point	D 6892	°C	-36
TBN	D 2896	g KOH/kg	10,2
Flash point COC	D 92	°C	216

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.