

## MULTIPURPOSE GREASE 2

DESCRIPTION:

This is a lubricating grease for general applications, where no specific requirements are asked. This grease has a good oxidation stability, so that it can insure a long-lasting lubrication. It is water-resistant and it has good temperature characteristics. Therefore it is useable at high temperatures and it stays pumpable at low temperatures.

APPLICATION:

This grease can be used for the most common applications in vehicles. It is also usable for the lubrication of lightly loaded components from machines, roller bearings, etc...

SPECIFICATION LEVEL:

	<u>MP2</u>	<u>MP3</u>
DIN 51502	K2K-30	K3K-30
ISO 6743	ISO-L-XCCEA2	ISO-L-XCCFA3

TYPICAL CHARACTERISTICS:

Test	Method	Unit	MP 2	MP 3
Colour			Amber	Amber
Texture			Smooth	Smooth
Soap type			Lithium	Lithium
NLGI-number	D217		2	3
Penetration after 60 strokes	ISO 2137	1/10 mm	265 - 295	220-250
Dropping point	IP 396	°C	>180	>180
Temperature range		°C	-30/+120 (max +130)	-30/+120 (max +130)
Four Ball Weld Load	DIN 51350:4	N	2000	2000

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.