

ALL-PURPOSE EP

DESCRIPTION:

These are semi-liquid Lithium greases, with NLGI-consistency 0, 00 and 000, which are specially designed for central lubricating units, like those applied on industrial machines and trucks.

These greases have excellent low temperature pumpability, where they maintain their good flow properties.

By the use of "Extreme Pressure "additives, these greases are resistant to heavy shocks and loads. They have also excellent anti-corrosion, anti-rust and anti-oxidant-properties, which increase the life span of the grease and the lubricated parts.

SPECIFICATION LEVEL:

	<u>NLGI 0</u>	<u>NLGI 00</u>	<u>NLGI 00/000</u>
DIN 51502	KP0K-30	KP00K-30	KP00G-30
ISO 6743	ISO-L-XCCFB0	ISO-L-XCCHB00	ISO-L-XCBEB00

TYPICAL VALUES:

Test	Method	Unit	0	00	00/000
Colour			Light brown	Dark brown	Amber
Soap type			Lithium	Lithium	Lithium
NLGI-numbers	D 217		0	00	00/000
Penetration after 60 strokes	ISO 2137	1/10 mm	355 - 385	400 - 430	400 - 475
Temperature range		°C	-30/+120 (max +130)	-30/+100	-40/+100 (max +110)
Drop point	IP 396	°C	> 160	> 160	> 160
Base oil viscosity	D 445	cSt	200	290	40
4-ball test, weld load	DIN 51350:4	N	2600	2600	2400

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.