

## CHAMPION SYNTOLUBE SL/CF 5W30

### DESCRIPTION :

Fully synthetic engine oil of the last generation, for the lubrication of all gasoline and diesel engines with turbocharging. Due to the excellent fluidity at low temperature and low resistance at start this product is fuel saving. Exceptional viscosity index and high thermal stability.

### APPLICATIONS :

This oil can be used in 4-stroke gasoline engines, four-valve, turbo.  
4-stroke diesel engines with or without turbo, without diesel particulate filter (DPF).

### SPECIFICATION LEVEL :

API	SL/CF
ACEA	A3/B4-08
MB	229.3
VW	502.00 / 505.00 / 501.01
BMW	LL-01
OPEL	GM-LL-B-025

### TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			5W30
Density at 15°C	D 4052	kg / m <sup>3</sup>	858
Viscosity at 40°C	D 445	cSt	66
Viscosity at 100°C	D 445	cSt	11,1
Viscosity at -30°C	D 5293	cP	6280
Viscosity index	D 2270		162
Pour point	D 6892	°C	-42
TBN	D 2896	g KOH/kg	10
Flash point COC	D 92	°C	214
Sulphated ash	D 874	mass %	1,0

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.