

CHAMPION SYNTOLUBE DC SL/CF 5W40

DESCRIPTION :

High performance engine oil of the latest generation, specially designed to meet the strict requirements of manufacturers and composed of non-conventional base oils and high quality additives.

APPLICATIONS :

This oil can be used in general in petrol engines of cars, which fulfills the highest performance and of diesel cars with turbo, and direct fuel injection. Extended drain intervals are possible, according to the specific recommendations of the constructors.

SPECIFICATION LEVEL :

| | | | |
|---------|--------------------|------|--------------------------|
| API | SJ/CF,SL/CF | VW | Approval 502.00 / 505.00 |
| ACEA | A3/B3-04, A3/B4-04 | BMW | Longlife |
| MB | Approval 229.3 | OPEL | GM-LL-B-025 |
| PORSCHE | approval | | |

TYPICAL CHARACTERISTICS :

| Test | Method | Unit | Average result |
|--------------------|--------|---------------------|----------------|
| SAE-class | | | 5W40 |
| Density at 15°C | D 4052 | kg / m ³ | 855 |
| Viscosity at 40°C | D 445 | cSt | 85 |
| Viscosity at 100°C | D 445 | cSt | 14,3 |
| Viscosity at -30°C | D 5293 | cP | 6300 |
| Viscosity index | D 2270 | | 175 |
| Pour point | D 6892 | °C | -42 |
| TBN | D 2896 | g KOH/kg | 10,0 |
| Flash point COC | D 92 | °C | 220 |
| Sulphated ash | D 874 | mass % | 1,1 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.