

CHAMPION SUPERLUBE SL/CF HC 10W40

DESCRIPTION :

Modern, semi-synthetic multigrade oil of the last generation, which was specially formulated for the lubrication of most 4-stroke petrol and diesel engines from passenger cars. By carefully selected base materials it satisfies the requirements of most manufacturers. It combines high performance with very low ash content.

APPLICATIONS :

This oil can be used in all passenger cars, equipped with petrol or diesel engines, where the constructor recommends one of the below specifications.

SPECIFICATION LEVEL :

API	SL/CF	VW	500.00/505.00
ACEA	A3/B3-04	MB	229.1

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			10W40
Density at 15°C	D 4052	kg / m ³	877
Viscosity at 40°C	D 445	cSt	95
Viscosity at 100°C	D 445	cSt	13,9
Viscosity at -25°C	D 5293	cP	6800
Viscosity index	D 2270		146
Pour point	D 6892	°C	-39
TBN	D 2896	g KOH/kg	7,6
Flash point COC	D 92	°C	220
Sulphated ash	D 874	mass %	0,95

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.