

## **CHAMPION MOTOR OIL SG/CD SAE 10W**

### DESCRIPTION :

Motor oils of high quality, suitable for diesel and gasoline engines (supercharged or naturally aspirated) from 1989 to 1996.

### APPLICATIONS:

This mono-grade oils are recommended for gasoline and diesel engines of cars, equipment for public works, and for mixed fleets of trucks and cars. The appropriate viscosity grade can be chosen according to the ambient temperature.

### SPECIFICATION LEVEL :

API	SG/CD	MIL	MIL-L-46152 E
CCMC	G4/PD2	MB	226.0

### TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result				
			10W	20W	30	40	50
SAE-class			10W	20W	30	40	50
Density at 15°C	D 4052	kg / m <sup>3</sup>	883	888	892	895	900
Viscosity at 40°C	D 445	cSt	36,7	57	98	150	210
Viscosity at 100°C	D 445	cSt	6,1	7,8	10,9	14,7	18,6
Viscosity index	D 2270		112	101	95	97	99
Pour point	D 6892	°C	-24	-22	-18	-9	-12
TBN	D 2896	g KOH/kg	5,3	5,3	5,3	5,3	5,3
Flash point COC	D 92	°C	212	220	235	240	240
Sulphated ash	D 874	mass %	1,2	1,2	1,2	1,2	1,2

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.