

## CHAMPION SYNTOLUBE 5W30 F 913

### DESCRIPTION :

This is a synthetic motor oil according to the specific requirements of the car manufacturer Ford. The use of specially selected additives provides excellent engine cleanliness and protects the exhaust catalyst. Due to its excellent fluidity, important fuel economy is obtained.

### APPLICATIONS :

This oil was specially developed for the lubrication of modern cars with gasoline, diesel or turbo engines where fuel economy is required.

### SPECIFICATION LEVEL :

API	SJ	FORD	WSS-M2C 913-A and B
ILSAC	GF-2		WSS-M2C 912-A
ACEA	A1-98/B1-98		WSS-M2C 912-A

### TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			5W30
Density at 15°C	D 4052	kg / m <sup>3</sup>	855
Viscosity at 40°C	D 445	cSt	56
Viscosity at 100°C	D 445	cSt	10,0
Viscosity at -30°C	D 5293	cP	4750
Viscosity index	D 2270		167
Pour point	D 6892	°C	-39
TBN	D 2896	g KOH/kg	10,4
Flash point COC	D 92	°C	230

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.