

CHAMPION SYNTOLUBE C1 5W30

DESCRIPTION :

Full synthetic, fuel economy "LOW SAPS" motor oil for gasoline/LPG and diesel engines of passenger cars with or without turbo.

APPLICATIONS :

This oil was especially designed for the newest generation (Euro 4) gasoline engines and diesel engines with diesel particulate filters (DPF), which require a low HTHS viscosity oil.

SPECIFICATION LEVEL :

ACEA	A1/B1-04 A5/B5-04 C1-07	MAZDA RENAULT JASO 2005	Service Fill RN 0700 DL-1
------	-------------------------------	-------------------------------	---------------------------------

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			5W30
Density at 15°C	D 4052	kg / m ³	848
Viscosity at 40°C	D 445	cSt	50
Viscosity at 100°C	D 445	cSt	9,45
Viscosity at -30°C	D 5293	cP	4200
Viscosity index	D 2270		170
Pour point	D 6892	°C	-36
TBN	D 2896	g KOH/kg	5,9
Flash point COC	D 92	°C	226
Sulphated ash	D 874	mass %	0,5

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.