

CHAMPION SYNTOLUBE C2 LE 5W30

DESCRIPTION :

This is a low viscosity synthetic "mid SAPS" engine oil of the latest generation, for the lubrication of gasoline and diesel cars, equipped with aftertreatment systems and which require a fuel economy oil.

APPLICATIONS :

It is especially recommended for the cars of the PSA group (Peugeot Citroën), where a low-emission engine oil is preferred. Its low ash content ensures optimum operation of the particulate filter (DPF).

SPECIFICATION LEVEL :

API	SM/CF
ACEA	C2-08, A1/B1-04, A5/B5-04
PSA	Oil meeting specification B71 2290
RENAULT	0700

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			5W30
Density at 15°C	D 4052	kg / m ³	856
Viscosity at 40°C	D 445	cSt	57
Viscosity at 100°C	D 445	cSt	10,1
Viscosity at -30°C	D 5293	cP	5500
Viscosity index	D 2270		167
Pour point	D 6892	°C	-39
TBN	D 2896	g KOH/kg	7,5
Flash point COC	D 92	°C	232
Sulphated ash	D 874	mass %	0,79

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.