

HYDROCRACKED BASED 10W40 SG/CD

DESCRIPTION :

This is a multigrade oil, based on hydrocracked base oil. The use of these special base oil in the formulation of this quality, ensures a high fluidity at low temperature, which not only makes the start easier, but realises also an immediately proper oil circulation and perfectly lubricates all the vital organs of the engines.

APPLICATIONS :

This oil was specially developed for the lubrication of all 4-stroke gasoline and diesel engines of cars, whether or not fitted with a turbocharger, and fulfils the the constructor's requirements from 1989 to 1996.

SPECIFICATION LEVEL :

API	SG/CD	MIL	MIL-L-46152 E
CCMC	G5/D2	MB	226.5

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			10W40
Density at 15°C	D 4052	kg / m ³	874
Viscosity at 40°C	D 445	cSt	97,5
Viscosity at 100°C	D 445	cSt	14,3
Viscosity at -25°C	D 5293	cP	6400
Viscosity index	D 2270		151
Sulphated ash	D 874	mass %	1,3
Flash point COC	D 92	°C	228
Pour point	D 6892	°C	-36
TBN	D 2896	g KOH/kg	5,3

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.