

## MULTIGRADE SG/CD SAE 15W40

### DESCRIPTION :

Mineral, super multi-grade engine oil for all light vehicles, petrol and oil diesel. This oil is characterized by a very good oxidation resistance, avoids "black sludge", a low sulphated ash and allows long oil drain periods, according to the prescription of the constructor.

### APPLICATIONS :

This oil is suitable for the lubrication of gasoline and light diesel engines, with or without turbo from 1989 to 1996. This oil fullfils the latest specifications CCMC.

### SPECIFICATION LEVEL :

API	SG/CD
CCMC	G4/D2
MIL	MIL-L-46152 E

### TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			15W40
Density at 15°C	D 4052	kg / m <sup>3</sup>	885
Viscosity at 40°C	D 445	cSt	103
Viscosity at 100°C	D 445	cSt	13,9
Viscosity at -20°C	D 5293	cP	6400
Viscosity index	D 2270		136
Pour point	D 6892	°C	-33
TBN	D 2896	g KOH/kg	5,3
Flash point COC	D 92	°C	216
Sulphated ash	D 874	Massa %	0,6

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.