

## MULTIGRADE PD-1 SF/CD SAE 15W40

### DESCRIPTION :

Multigrade engine oil for the lubrication of gasoline and diesel engines of passenger cars with natural aspiration or turbocharging. This oil is characterized by a combination of good detergent and dispersion properties, together with a low ash content.

### APPLICATIONS :

This oil fulfills the requirements of the European Constructors (CCMC) and is suitable for the lubrication of gasoline and diesel engines, with or without turbo from 1980 to 1989.

### SPECIFICATION LEVEL :

API	SF/CD	FORD	SSM-2C 9011A
CCMC	G2/PD1	VW	501.01

### TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			15W40
Density at 15°C	D 4052	kg / m <sup>3</sup>	882
Viscosity at 40°C	D 445	cSt	105
Viscosity at 100°C	D 445	cSt	14,0
Viscosity at -20°C	D 5293	cP	6340
Viscosity index	D 2270		135
Pour point	D 6892	°C	-36
TBN	D 2896	g KOH/kg	5,5
Flash point COC	D 92	°C	218
Sulphated ash	D 874	mass %	0,55

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.