

MULTIGRADE SL/CF SAE 10W40

DESCRIPTION :

Semi-synthetic multigrade oil of the highest quality. Compared with mineral oils it is distinguished by a higher resistance to temperature variations and ageing. Its new composition ensures optimum cleanliness of the engine, under all circumstances. Catalyst friendly.

APPLICATIONS :

Specially designed for the lubrication of all 4-stroke petrol and diesel engines of cars, whether or not fitted with turbo engines, and which meets the specifications listed below.

SPECIFICATION LEVEL :

API	SL/CF	MB	229.1
ACEA	A3-02/B3-98#2	VW	500.00/505.00

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			10W40
Density at 15°C	D 4052	kg / m ³	875
Viscosity at -25°C	D 5293	cP	6300
Viscosity at 40°C	D 445	cSt	96,5
Viscosity at 100°C	D 445	cSt	14,3
Viscosity index	D 2270		153
Pour point	D 6892	°C	-39
TBN	D 2896	g KOH/kg	7,6
Flash point COC	D 92	°C	220
Sulphated ash	D 874	mass %	0,95

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.