

MULTIGRADE SL/CF SAE 15W50 SS

DESCRIPTION:

Multigrade semi-synthetic oil of the highest quality. Compared with mineral oils, it distinguishes itself by an improved resistance against high temperature and ageing. Its renewed composition ensures optimal cleanliness of the engine in all conditions. The oil protects the catalyst and ensures optimal engine protection.

APPLICATIONS:

This oil was specially developed for the lubrication of all 4-stroke gasoline or diesel, supercharged (turbo) or naturally aspirated and fullfils the latest norms of the constructors.

SPECIFICATION LEVEL:

API	SL/CF
ACEA	A3/B3-08, A3/B4-08
MB	229.1

TYPICAL CHARACTERISTICS:

Test	Method	Unit	Average result
SAE-class			15W50
Density at 15°C	D 4052	kg / m ³	880
Viscosity at 40°C	D 445	cSt	134
Viscosity at 100°C	D 445	cSt	18,0
Viscosity at -20°C	D 5293	cP	6600
Viscosity index	D 2270		150
Pour point	D 6892	°C	-39
TBN	D 2896	g KOH/kg	8,3
Flash point COC	D 92	°C	225
Sulphated ash	D 874	Mass %	1,03

We reserve the right to alter the general characteristics of our products to let our customers benefit of the latest technical evolutions.