

MULTIGRADE SL/CF SAE 5W30

DESCRIPTION :

Synthetic motor oil from the latest generation, for the lubrication of all gasoline and diesel engines with turbocharging. Through its special composition with a friction improver (friction modifier), fuel savings can be realized. Her excellent fluidity at low temperature gives a very low resistance when starting the engine, hereby reducing wearing to a minimum.

APPLICATIONS :

This oil can be used in modern gasoline and diesel engines without particulate filters for cars, where an ACEA A1, A5, B1 or B5 level is required.

SPECIFICATION LEVEL :

API	SL/CF
ACEA	A5/B5-04, A5/B5-08
RENAULT	RN 0700

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			5W30
Density at 15°C	D 4052	kg / m ³	857
Viscosity at 40°C	D 445	cSt	60
Viscosity at 100°C	D 445	cSt	10,2
Viscosity at -30°C	D 5293	cP	6300
Viscosity index	D 2270		158
Pour point	D 6892	°C	-39
TBN	D 2896	g KOH/kg	8,2
Flash point COC	D 92	°C	225
Sulphated ash	D 874	mass %	0,97

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.