

MULTIGRADE SM/CF C2 SAE 5W30 FE

DESCRIPTION :

100% synthetic engine oil with low viscosity of the latest generation, for the lubrication of all gasoline and diesel passenger cars, equipped with aftertreatment systems. The low ash formulation (MID SAPS) protects the engine and catalyst system. This quality is distinguished by her improved fuel-saving behavior, excellent fluidity at low temperatures and extremely low resistance at start. It allows long drain intervals.

APPLICATIONS :

Euro 4 engines from petrol and diesel cars, where low viscosity oils (ACEA C2) with low ash content are required.

SPECIFICATION LEVEL :

API	SM/CF, SL, SJ
ACEA	A1/B1-04, A5/B5-04, C2-08
RENAULT	RN 0700

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			5W30
Density at 15°C	D 4052	kg / m ³	850
Viscosity at 40°C	D 445	cSt	57
Viscosity at 100°C	D 445	cSt	10,1
Viscosity at -30°C	D 5293	cP	4700
Viscosity index	D 2270		170
Pour point	D 6892	°C	-39
TBN	D 2896	g KOH/kg	7,9
Flash point COC	D 92	°C	214
Sulphated ash	D 874	mass %	0,8

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.