

## HYDROCRACKED BASED SL/CF 5W40

DESCRIPTION :

Synthetic based engine oil for the lubrication of most petrol and diesel engines with turbocharging.

APPLICATIONS :

This oil can be used in 4-stroke petrol engines, multi valves, and turbo 4-stroke diesel engines, with or without turbo. This type of engine oil is not suitable for diesel engines with particulate traps and allows no extended drain intervals.

SPECIFICATION LEVEL :

API	SL/CF,SJ,CD	VW	502.00 / 505.00 (1/97)
ACEA	A3/B3-04	PORSCHE	
MB	229.1		

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			5W40
Density at 15°C	D 4052	kg / m <sup>3</sup>	857
Viscosity at 40°C	D 445	cSt	88
Viscosity at 100°C	D 445	cSt	14,0
Viscosity at -30°C	D 5293	cP	5800
Viscosity index	D 2270		167
Pour point	D 6892	°C	-39
TBN	D 2896	g KOH/kg	9,5
Flash point COC	D 92	°C	235
Sulphated ash	D 874	mass %	1,0

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.