

## MULTIGRADE MS-F SAE 5W30

### DESCRIPTION :

This is a very high quality motoroil, which was especially developed for the requirements of the Ford specification WSS-M2C-913-C. It is characterized by highly improved lubricating properties and provides Fuel Economy (>3%).  
This oil replaces the M2C-913-A/B specifications.

### APPLICATIONS :

It is mandatory for all Ford models (gasoline and diesel, also those with particulate filter) from 2009 on, with the exception of the models which are equipped with pump injectors (Galaxy I en II) and Ford KA (diesel and gasoline from 2009).

### SPECIFICATION LEVEL :

API	SL/CF
ACEA	A1/B1-08 A5/B5-08
FORD	WSS-M2C-913-C
RENAULT	RN 0700

### TYPICAL CHARACTERISTICS:

Test	Method	Unit	Average result
SAE-class			5W30
Density by 15°C	D 4052	kg / m <sup>3</sup>	852
Viscosity at 40°C	D 445	cSt	52,0
Viscosity at 100°C	D 445	cSt	9,6
Viscosity at -30°C	D 5293	cP	4000
Viscosity index	D 2270		172
Pour point	D 6892	°C	-39
TBN	D 2896	g KOH/kg	10,1
Flash point COC	D 92	°C	218
Sulphated ash	D 874	mass %	1,09

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.