

ATF DEXRON II

DESCRIPTION :

This is an oil with a high viscosity index for automatic transmissions. It is characterized by a high chemical stability, increased anti-wear properties and an excellent resistance against ageing.

APPLICATIONS :

It can be used in automatic transmissions, torque convertors, power steering and hydraulic circuits, for which the manufacturers prescribe a product, which meets the GENERAL MOTORS ATF TYPE DEXRON IID-requirements.

SPECIFICATION LEVEL:

MB	236.1, 236.5, 236.6, 236.7	FORD	M2C 166H, Mercon
MAN	339 D	VOITH	55.6335 (G 607)
CAT	TO-2	ALLISON	C4
GM	6137-M DEXRON ® II-D	ZF	TE-ML 02F, 03D, 04D, 09, 11A, 14A, 17C

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
Colour			red
Density at 15°C	D 4052	kg / m ³	865
Viscosity at 40°C	D 445	cSt	37
Viscosity at 100°C	D 445	cSt	7,4
Viscosity at -40	D 2893	cP	45.000
Viscosity index	D 2270		170
Pour point	D 6892	°C	-39
TBN	D 2896	g KOH/kg	3,0

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.