

WOLF MULTIGEAR GL4

DESCRIPTION:

These are mechanical gear oils with moderate "extreme pressure" characteristics and were specially developed to avoid corrosion of copper alloys.

APPLICATIONS:

They are suitable for the lubrication of synchromesh gearboxes, transfer boxes, mechanical steering controls and most of the rear axles (certain rear axles should be run in with a GL5 oil).

SPECIFICATION LEVEL:

API	GL 4
MIL	MIL-L-2105

TYPICAL CHARACTERISTICS:

Test	Methode	Eenheid	Gemiddeld resultaat			
			80W	80W90	85W90	85W140
SAE KLASSE			80W	80W90	85W90	85W140
Dichtheid bij 15°C	D 4052	kg/m ³	883	892	899	900
Viscositeit bij 40°C	D 445	cSt	70	148	175,3	420
Viscositeit bij 100°C	D 445	cSt	9,2	14,7	17,6	26
Viscositeitsindex	D 2270		107	98	109	82
Vlampunt COC	D 92	°C	195	224	210	215
Stolpunt	D 6892	°C	-33	-30	-20	-18
Corrosie CU	D 130		1A	1A	1A	1A

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

2201 - 2208 - 2210 - 2207

March, 2010