

WOLF HD POLYGEAR GL 5

DESCRIPTION :

These are extreme-pressure lubricants for gear boxes, specially formulated to satisfy the highest service conditions: high speed, shockloads and high torque at low speeds.

APPLICATIONS :

These are recommended for all hypoid transmissions and are also suitable for spiral bevel gears, worm wheels and most transaxles.

SPECIFICATION LEVEL:

API	GL 5
MIL	MIL-L-2105 C and D
MAN	342N (SAE 80W90)
ZF TE-ML	05A, 07A, 12E, 16C, 17B, 19B 16B: SAE 80W90 16D: SAE 80W140, 85W140

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result		
			80W90	80W140	85W140
SAE-CLASS			80W90	80W140	85W140
Density at 15°C	D 4052	kg / m ³	896	900	908
Viscosity at 40°C	D 445	cSt	147	205	367
Viscosity at 100°C	D 445	cSt	14,7	29,7	26,1
Viscosity index	D 2270		99	186	95
Flash point COC	D 92	°C	210	215	215
Pour point	D 6892	°C	-33	-39	-15
Corrosion Cu	D 130		1B	1B	1B

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

2308 - 2311 - 2309

Maart, 2010.