

TWO STROKE UNIVERSAL BIO

DESCRIPTION :

Fully synthetic oil for water-cooled 2-stroke gasoline engines, with a very high output and which also can be used for air-cooled engines. Biodegradable and universally applicable, this oil is suited for machines where the tank is filled with a mixture of gasoline and oil, and for those with separate oil reservoirs. Easily miscible with gasoline and excellent protection against rust and deposits.

APPLICATIONS :

This oil is applicable for all water-cooled 2-stroke gasoline engines with a dilution level of 2% (1 in 50) and 1% (1 in 100), and in accordance with the requirements of manufacturers and the instructions (competition). Because of its universality, it can be used for outboard engines, jet skis, personal watercraft, etc., as well as cross, trial, ULM, etc...

SPECIFICATION LEVEL :

NMMA	TC-W3
API	TC+
CEC	L-33-T-82 biodegradability > 80%.

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
Colour			green
Density at 15°C	D 4052	kg / m ³	897
Viscosity at 40°C	D 445	cSt	47
Viscosity at 100°C	D 445	cSt	8,5
Viscosity index	D 2270		160
Pour point	D 6892	°C	-36
TBN	D 2896	g KOH/kg	9,6
Flash point COC	D 92	°C	105

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.