

# **WOLF RADIATOR COOLANT STANDARD** **-36°C**

DESCRIPTION :

This is an anti-freeze solution, based on mono-ethyleneglycol and anti-corrosion additives in demineralised water. It contains no nitrites, amines nor phosphates and gives an excellent protection against corrosion, no deposit formation. Easy to apply, the solution is already prepared.

APPLICATIONS :

This liquid can be used in cooling circuits of the open or closed type with a protection against freezing until -36°C. Can be used during the whole year.

SPECIFICATION LEVEL :

ASTM	D 3306-74	DB	DBL-7700
GME	13.368	FORD	SSM-97B9102A
MIL	0-A-00548 C	BMW	N600.69.0
MAN	324	RENAULT	RVI
VW	TL-VW774	SAAB/SCANIA	S 28917.3
FIAT	55523/1		

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
Colour			Blue
Density at 15°C	D 4052	kg / m <sup>3</sup>	1065
Protection temperature	D 1177	°C	-36
Water content	DIN 51777 T1	%	52
Reserve alcalinity	D 1121	0,1N/HCl	11,5
pH	D 1287		8,7

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.