

MULTIGRADE SL/CF SAE 5W20

03/07/2016
14114

This is a full synthetic motor oil, specifically developed for the requirements of the Ford WSS-M2C925-B specification. It is characterized by significantly improved lubricating properties and provides a very high level of Fuel Economy (>3%). It also meets the engine test requirements of ACEA A5/B5.

APPLICATIONS

It is mandatory for the Ford 1.6 16V Ti-VCT and 1.6 EcoBoost/ECONetic gasoline engines. This engine oil can also be used where ILSAC GF-4 oils are recommended, and for Jaguar and LandRover vehicles, requiring the WSS-M2C925-A specification.

FEATURES

Total engine protection : performance in keeping the engine clean.
Cold start : excellent fluidity at low temperature.
Fuel economy: superior fuel economy and CO2 reduction.

SPECIFICATION LEVEL

ACEA	A1/B1-12	FORD	WSS-M2C925-A
API	SL/CF	FORD	WSS-M2C925-B
FORD	M2C-925-B		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.851
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	43.0
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	8
Viscosity index	ASTM D2270		161
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	10.1
Pour point	ASTM D6892	°C	-48
CCS viscosity at -30°C	ASTM D5293	mPa.s	3600
Sulfated Ash	ASTM D874	Mass %	1.09
Flash Point COC	ASTM D92	°C	210

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.